

BSN M536 RFID Inlay

BSN RFID Product Spec Sheet






Inlay Size: 50x30mm

Web Width 68mm

RF Sensitivity
Performance:

Orientation Read Range (m)



Test power : 5~30dbm; Frequency860-960MHz ; Step 5MHz&0.1 dB

Market Applications:

- Apparel & Footwear
- Luxury Goods
- Food

Notes:

⚠RFID inlays are sensitive to ESD. Observe standard industry practices relating to electronics/RFID to keep environmental impact and static charge to a minimum.

Attributes	BSN M536 RFID Inlay
Operating Frequency	860MHz-960MHz
Antenna Size	50x30mm
Web Width	68mm
Integrated Circuit(IC)	IMPINJ Monza R6
EPC Memory	96 bits
Inlay Substrate Material	PET
RF Protocol	EPC Class1 Gen2\ISO/IEC 18000-6C
Operating Temperature	-5 °C to 60 °C / 23 °F to 140 °F
Operating Humidity	20% ~ 60% RH
ESD Voltage Immunity	Max. 2000V


Web site: www.gzbsn.com

Copyright ©2018 Baoshen Group. All rights reserved

BSN M536 RFID Inlay

BSN RFID Product Spec Sheet

BSN M536 Dry Inlay Web 68mm



BSN M536 Wet Inlay Web 57mm

